

CPC-CPD Belt 50 Hertz

Type	l/min	cfm	HP	kW	Bar	Start	dB(A) Silenced	kg	L x W x H (mm)
Basemounted 400/3/50									
CPC 40/8	4920	174	40	30	8	Y/D	71	748	1247x 1060 x 1630
CPC 40/10	4320	153	40	30	10	Y/D	69	748	1247x 1060 x 1630
CPC 40/13	3480	123	40	30	13	Y/D	69	748	1247x 1060 x 1630
CPC 50/8	6120	216	50	37	8	Y/D	71	832	1247x 1060 x 1630
CPC 50/10	5520	195	50	37	10	Y/D	70	832	1247x 1060 x 1630
CPC 50/13	4260	150	50	37	13	Y/D	70	832	1247x 1060 x 1630
CPC 60/8	7800	275	60	45	8	Y/D	72	862	1247x 1060 x 1630
CPC 60/10	6840	242	60	45	10	Y/D	71	862	1247x 1060 x 1630
CPC 60/13	5700	201	60	45	13	Y/D	71	862	1247x 1060 x 1630
CPD 75/8	8700	307	75	55	8	Y/D	72	1073	1420x 1060 x 1630
CPD 75/10	7920	280	75	55	10	Y/D	71	1073	1420x 1060 x 1630
CPD 75/13	7080	250	75	55	13	Y/D	71	1073	1420x 1060 x 1630
CPD 100/8	11520	407	100	75	8	Y/D	75	1280	1660x 1060 x 1630
CPD 100/10	10080	356	100	75	10	Y/D	74	1280	1660x 1060 x 1630
CPD 100/13	8880	314	100	75	13	Y/D	74	1280	1660x 1060 x 1630