

## CPC-CPD-CPE Gear 50 Hertz

Type	l/min	cfm	HP	kW	Bar	Start	dB(A) Silenced	kg	L x W x H (mm)
<b>Base mounted 400/3/50</b>									
CPC 40/7	5460	193	40	30	7	Y/D	69	760	1420x 1060 x 1630
CPC 40/8	5100	180	40	30	8	Y/D	69	760	1420x 1060 x 1630
CPC 40/10	4560	161	40	30	10	Y/D	68	760	1420x 1060 x 1630
CPC 40/13	3840	136	40	30	13	Y/D	68	760	1420x 1060 x 1630
CPC 50/7	6720	237	50	37	7	Y/D	71	840	1420x 1060 x 1630
CPC 50/8	6420	227	50	37	8	Y/D	71	840	1420x 1060 x 1630
CPC 50/10	5760	203	50	37	10	Y/D	70	840	1420x 1060 x 1630
CPC 50/13	4620	163	50	37	13	Y/D	70	840	1420x 1060 x 1630
CPC 60/7	7860	278	60	45	7	Y/D	72	845	1420x 1060 x 1630
CPC 60/8	7620	269	60	45	8	Y/D	72	845	1420x 1060 x 1630
CPC 60/10	6960	246	60	45	10	Y/D	71	845	1420x 1060 x 1630
CPC 60/13	5940	210	60	45	13	Y/D	71	845	1420x 1060 x 1630
CPD 75/7	12540	443	75	55	7	Y/D	72	1100	1660x 1060 x 1630
CPD 75/8	11940	422	75	55	8	Y/D	72	1100	1660x 1060 x 1630
CPD 75/10	10740	379	75	55	10	Y/D	71	1100	1660x 1060 x 1630
CPD 75/13	9420	333	75	55	13	Y/D	71	1100	1660x 1060 x 1630
CPD 100/7	14280	504	100	75	7	Y/D	75	1287	1660x 1060 x 1630
CPD 100/8	13500	477	100	75	8	Y/D	75	1287	1660x 1060 x 1630
CPD 100/10	12000	424	100	75	10	Y/D	74	1287	1660x 1060 x 1630
CPD 100/13	10140	358	100	75	13	Y/D	74	1287	1660x 1060 x 1630
CPE 100/7	14280	504	100	75	7	Y/D	72	1540	1860x 1060 x 1630
CPE 100/8	13500	477	100	75	8	Y/D	72	1540	1860x 1060 x 1630

## CPC-CPD-CPE Gear 50 Hertz

Type	l/min	cfm	HP	kW	Bar	Start	dB(A) Silenced	kg	L x W x H (mm)
<b>Base mounted 400/3/50</b>									
CPE 100/10	12000	424	100	75	10	Y/D	71	1540	1860x 1060 x 1630
CPE 100/13	10140	358	100	75	13	Y/D	71	1540	1860x 1060 x 1630
CPE 120/7	15720	555	125	90	7	Y/D	74	1570	1860x 1060 x 1630
CPE 120/8	15600	551	125	90	8	Y/D	74	1570	1860x 1060 x 1630
CPE 120/10	14220	502	125	90	10	Y/D	73	1570	1860x 1060 x 1630
CPE 120/13	11640	411	125	90	13	Y/D	73	1280	1860x 1060 x 1630