

CPVS (30-90) 50 Hertz



Type	m ³ /h	l/min	cfm	HP	kW	Bar	dB(A)	kg	L x W x H (mm)
Base mounted 400/3/50 + Inverter									
CPVS 40	326	5460	192	40	30	7	69	810	1420x1060x1630
	275	4560	162	40	30	9,5			
	267	4440	157	40	30	10			
CPVS 50	402	6720	236	50	37	7	71	890	1420x1060x1630
	347	5760	204	50	37	9,5			
	336	5580	198	50	37	10			
CPVS 60	470	7860	277	60	45	7	72	895	1420x1060x1630
	419	6960	247	60	45	9,5			
	406	6780	239	60	45	10			
CPVS 75	577	9600	340	75	55	7	72	1170	1660x1060x1630
	504	8400	297	75	55	9,5			
	489	8160	288	75	55	10			
CPVS 95	751	12540	442	100	75	7	75	1357	1660x1060x1630
	643	10740	379	100	75	9,5			
	624	10380	367	100	75	10			
CPVS 100	856	14280	504	100	75	7	72	1610	1860x1060x1630
	720	12000	424	100	75	9,5			
	698	11640	411	100	75	10			
CPVS 125	944	15720	556	125	90	7	74	1640	1860x1060x1630
	854	14220	503	125	90	9,5			
	828	13800	488	125	90	10			